

# Wood<sup>®</sup> Welded

## SUBMITTAL DATA:

**MATERIAL:** HARD MAPLE. KILN DRIED TO 6 TO 8 % MOISTURE CONTENT.

**FABRICATION:** FABRICATED FROM WOOD STRIPS NOT MORE THAN 1 7/8 " WIDE. FINGER JOINT MATERIAL MAY BE USED FOR SIZES OVER 7 FOOT. TOPS OVER 12 FEET IN LENGTH WILL BE MANUFACTURED IN SECTIONS AND JOINED IN THE FIELD WITH "C.Q. FASTENERS.

GLUED UNDER PRESSURE USING RADIO FREQUENCY.

**SIZE TOLERANCE:** LENGTH, +/- 1 / 8 "  
WIDTH, +/- 1 / 8 "  
THICKNESS, +/- 1 / 16 "

SANDED WITH 120 GRIT PAPER.

**FINISH:** " DURAKRYL 102 " U.V. CURED POLYURETHANE.  
" DURAKRYL 102 " MEETS OR EXCEEDS THE K.C.M.A.ANSI  
A161.1-1995 PERFORMANCE & CONSTRUCTION STANDARD

**CURBS:** SOILD HARD MAPLE, 4"X 3 / 4 WITH DURAKRYL 102 FINISH

TOPS OVER 1 3 / 4 " IN THICKNESS AND OVER 72 " IN LENGTH WILL HAVE FINGER JOINTS APPEAR IN THE FACE "EUROPEAN STITCH".

MICHIGAN MAPLE BLOCK DOES NOT SELECT FOR COLOR. WE USE THE FULL LOG RUN. MINERAL AND OTHER NATURAL OCCURING VARIATIONS IN COLOR, GRAIN ECT. ARE NOT CONSIDERED DEFECTS. BUTCHER BLOCK PRODUCTS ARE REAL WOOD , AND JUST AS NO TWO TREES IN NATURE ARE ALIKE NO TWO BUTCHER BLOCK TOPS ARE ALIKE.

### Michigan Maple Block Co.

1420 Standish Ave  
Petoskey, MI. 49770  
231.347.4170

[www.mapleblock.com](http://www.mapleblock.com)

